

<b>Author:</b>	R.Knox
<b>Page</b>	1
<b>Document Number</b>	QUA-Forms-12
<b>Revision</b>	2
<b>Effective Date</b>	25/05/2021

Property	Unit	Limits		Test Method
		Minimum	Maximum	
Fatty Acid Methyl Ester (FAME)Content	%(V/V)	14	20	EN14078
Water Content	%(m/m)		0.026	EN ISO 12937
Sulfur Content	mg/kg		10	EN ISO 20846
Density at 15°C	Kg/m <sup>3</sup>	820,0	860,0	EN ISO 3675
Cetane Number		51		EN ISO 5165
Polycyclic aromatic hydrocarbons	%(m/m)		8	EN 12916
Manganese Content			2	Pr EN 16576
Flash point	°C	>55.0	-	EN ISO 2719
Ash Content	%(m/m)	-	0.010	EN ISO 6245
Total Contamination	mg/kg	-	24	EN 12662
Oxidation Stability	H	20	-	EN 15751
Viscosity at 40°C	mm <sup>2</sup> /s	2.000	4.620	EN ISO 3104
<b>Distillation</b>				
% (V/V) recovered at 250°C	%(V/V)		<65	EN ISO 3405
% (V/V) recovered at 350°C	%(V/V)	85		
95% (V/V) recovered at	°C		360	

**Climate Dependent Requirements and related Test Methods**

Property	Unit	Limits		Test Method
		Grade C*	Grade E**	
CFPP °C	°C	-5	-15	EN 116

\*Argent will supply Grade C from 16<sup>th</sup> March to the 31<sup>st</sup> October inclusive.

\*\*Argent will supply Grade E from 1<sup>st</sup> of November to the 15<sup>th</sup> March inclusive.

Comments: -

- The above table is taken from BS EN 16709.

<b>Issue Status</b> If printed this document becomes an "uncontrolled copy" and will not be subject to update unless over stamped as a "Controlled Copy"	<b>Author:</b>
	<b>Raymond Knox</b>